




APRO IR



Rivelatore all'infrarosso attivo per comando porte automatiche
Infrared microwave detector for controlling automatic doors
Detector a infrarrojo activo para el control de puertas automáticas

	APRO IR
Tensione di alimentazione <i>Power voltage</i> Tensión de alimentación	12 - 24 V _{AC} 12 - 30 V _{DC}
Assorbimento <i>Consumption</i> <i>Consumo</i>	250 mA max
Contatto di uscita <i>Output contact</i> Contacto de salida	N.O. (cavi colore giallo <i>yellow wires</i>) (cables color amarillo)
Portata <i>Range</i> Alcance	0,4 - 1,05 m regolabile/ <i>adjustable</i> /regulable
Durata comando relè <i>Relais control time</i> Duración del relé de control	2 - 7 secondi regolabile <i>seconds adjustable</i> /segundos regulable
Grado di protezione <i>Degree of protection</i> Grado de protección	IP 45
Altezza di installazione <i>Installation height</i> Altura de instalación	2,5 m max
Area di rilevazione <i>Detection area</i> <i>Área de detección</i>	regolabile mediante trimmer <i>Adjustable by trimmer</i> regulable mediante potenciómetro
Contatto relè <i>Relay contact</i> Contacto de relé	0,5 A - 24 V AC-DC
Orientabilità verticale <i>Vertical directionality</i> Orientación horizontal	5 - 24° regolabile/ <i>adjustable</i> /regulable
Temperatura di funzionamento <i>Operating temperature</i> Temperatura de funcionamiento	- 20 ° C / + 55 ° C
Garanzia <i>Warranty</i> Garantía	24 mesi/ <i>months</i> /meses



Copertura
Range - Alcance